

FREE-SPACE ISOLATOR: (CORE) POLARIZATION-INDEPENDENT (1064nm)

Specifications

Contact Ascentta with your custom specification needs.

Parameter		Unit	Single Stage	Dual Stage	
Wavelength		nm	1064±5nm		
Isolation	(λ , 23°C)	Typ.	dB	40	55
	(23°C)	Min	dB	28	42
Insertion Loss	(λ , 23°C)	Typ.	dB	1.3	2.4
	(23°C)	Max	dB	1.5	2.6
PDL		Max	dB	0.05	
PMD		Max	ps	0.1/0.25*	0.1
Optical Power Handling		Max	W/cm2	10	
Operating Temperature			°C	-5 to 85	
Storage Temperature			°C	-40 to +85	

* Max PMD is 0.25 for non-compensated single-stage parts.

Ordering Information

Contact Ascentta with your custom configuration needs.

FSI	Type	Stages Or Layers	Packaging	Wavelength	Clear Aperture	Package Dimension
FSI	PI=Polarization Independent	S=Single Stage D=Dual Stage	N=Non-latched (with Magnet Ring)	10=1064nm X=Others	05=0.5mm 09=0.9mm 12=1.2mm X=Others	Contact us with your requirements

Package Dimensions

Contact us with your requirements.

