

JUMPER CABLE / PATCH CORD (FC, SC, LC, ST)

Specifications

Contact Ascentta with your custom specification needs.

Parameter		Unit	PC	APC
Insertion Loss (23°C, All SOP)	Max	dB	0.2	0.25
Return Loss	Min	dB	40	60
Exchange	Max	dB	0.2	
Repeatability	Max	dB	0.2	
Durability	Min	Cycles	1000	
Optical Power Handling	Max	mW	300	
Operating Temperature		°C	-20 to 85	
Storage Temperature		°C	-40 to 85	

* SOP-State Of Polarization

Ordering Information

Contact Ascentta with your custom configuration needs.

JP	Fiber Type	Connector-1	Connector-2	Cable Type	Fiber Length
JP	S=SMF-28	FC=FC/PC	FC=FC/PC	B= 250um	10=1.0m
	F1=1060 Flex core	FA=FC/APC	FA=FC/APC	L= 900um	15=1.5m
	H1=Hi-1060	LC=LC/PC	LC=LC/PC	W=2mm	20=2.0m
		LA=LC/APC	LA=LC/APC	H=3mm	30=3.0m
	X=Others	SC=SC/PC	SC=SC/PC	X=Others	X=Others
	SA=SC/APC	SA=SC/APC			
	ST=ST/PC	ST=ST/PC			
	X=Others	X=Others			