

JUMPER CABLE / PATCH CORD (MTRJ)

Specifications

Contact Ascentta with your custom specification needs.

| Parameter | Unit | Value |
|--------------------------------|------------|------------|
| Insertion Loss (23°C, All SOP) | Max dB | 0.5 |
| Return Loss | Min dB | 35 |
| Exchange | Max dB | 0.3 |
| Repeatability | Max dB | 0.3 |
| Durability | Min Cycles | 1000 |
| Optical Power Handling | Max mW | 300 |
| Operating Temperature | °C | -20 to +85 |
| Storage Temperature | °C | -40 to +85 |

* SOP=State Of Polarization

Ordering Information

Contact Ascentta with your custom configuration needs.

| JP | Fiber | Connector-1 | Connector-2 | Cable Type | Fiber Length |
|----|------------------|-------------|-------------|------------|--------------|
| JP | S=SMF-28 | FC=FC/PC | FC=FC/PC | B=250um | 10=1.0m |
| | F1=1060 Flexcore | FA=FC/APC | FA=FC/APC | L=900um | 20=2.0m |
| | H1=Hi-1060 | LC=LC/PC | LC=LC/PC | W=2mm | 30=3.0m |
| | | LA=LC/APC | LA=LC/APC | H=3mm | 35=3.5m |
| | X=Others | MC=MU/PC | MC=MU/PC | | |
| | | MA=MU/APC | MA=MU/APC | X=Others | X=Others |
| | | SC=SC/PC | SC=SC/PC | | |
| | | SA=SC/APC | SA=SC/APC | | |
| | | ST=ST/PC | ST=ST/PC | | |
| | | MTRJ=MTRJ | MTRJ=MTRJ | | |
| | D4=D4 | D4=D4 | | | |
| | X=Others | X=Others | | | |

Contact Ascentta for all your custom design needs.